

Product Information Sheet

Ri-Jet Eco Print

This special PVC FREE material is ideal for those clients seeking a more environmentally friendly approach to their displays.

Advantages over PVC are:

Phthalates free, which can be harmful to your health. Low shrinkage and low flammability.

Suitable for solvent, eco-solvent inkjet printing and UV based systems.

Product Type	PVC free Polyolefin film for solvent inkjet printing.
Face Film	50 µm (+/- 10%) Matt White Polyolefin.
Adhesive	Solvent based acrylic, grey permanent. Medium Tack High Cohesion Ultimate adhesion FINAT1 >13N / 25mm ²
Liner	144gsm Chlorinefree bleached kraftpaper, with solventfree siliconization, two sided PE coating stabilized with excellent Lay-flat properties
Application Temperature	Min +10°C
Service Temperature	-20°C—+120°C
Chemical Resistance	No effect when tested with Detergent (24hrs), Petroleum (1hr), Motor Oil (24hrs).
Storage	Under normal conditions - i.e. 50% relative humidity and room temperatures of approx. 20°C this product in its original packaging can be stored up to 12 months after delivery.
Note	The technical information here is true to the best of our present knowledge. However, it shall not constitute a guarantee for any specific product feature and shall not establish a legally valid contractual relationship. We recommend the customer to test the suitability of the product for the required purposes under original conditions

If you need any further information please call our team on 0845 165 1636

Unit 1, Albany Court
Albany Road
Market Harborough
Leicestershire
LE16 7QP

Phone: 01858 431642
Fax: 01858 466992
Email: sales@dorotape.co.uk

