

## Product Information Sheet

### Vehicle Lam

This ultra thin overlamination film is a 30 micron cast vinyl. This conformable film is therefore ideal for vehicle wrapping applications and used in conjunction with VWS2 or similar cast vinyls.

|                                |   |
|--------------------------------|---|
| <b>Product Type</b>            | Cast PVC overlamination film.   |
| <b>Face Film</b>               | 30 µm Cast clear gloss  |
| <b>Adhesive</b>                | Permanent acrylic (solvent based).<br>High tack<br>Good cohesion  |
| <b>Liner</b>                   | 144gsm 2 side PE coated white kraft paper   |
| <b>Application Temperature</b> | Min +10°C   |
| <b>Service Temperature</b>     | -20°C—+120°C  |
| <b>Chemical Resistance</b>     | Resistant to detergent, gasoline and motor oil  |
| <b>Storage</b>                 | Under normal conditions - i.e. 50% relative humidity and room temperatures of approx. 20°C this product in its original packaging can be stored up to 12 months after delivery.   |
| <b>Note</b>                    | The technical information here is true to the best of our present knowledge. However, it shall not constitute a guarantee for any specific product feature and shall not establish a legally valid contractual relationship. We recommend the customer to test the suitability of the product for the required purposes under original conditions |

If you need any further information please call our team on 0845 165 1636

Unit 1, Albany Court  
Albany Road  
Market Harborough  
Leicestershire  
LE16 7QP

Phone: 01858 431642  
Fax: 01858 466992  
Email: sales@dorotape.co.uk